



– RELIABLE  
WOOD  
CHIPPING

# REDLINE 320/8 CHIPPER COMBI



## SPECIFICATIONS - "REDLINE CHIPPER COMBI" 320/8

|                             |                                 |                                     |
|-----------------------------|---------------------------------|-------------------------------------|
| In feed opening             | 32x34 cm between the rollers    | 32 x 72 on end of in feed table     |
| Rotor disc diameter         | 1050 mm                         | Rotor disc weight 434 kg            |
| Number of blades 360°       | 4 (2 cuts per round)            | Principle: "TP Opticut"             |
| In feed rollers             | 2 vertical                      | Std. TP-Pilot K                     |
| In feed table               | Hydraulic foldable              | Opt. Screening slots                |
| Vehicle width               | Ca. 200 cm                      |                                     |
| Vehicle length              | Ca. 625 cm                      |                                     |
| Vehicle height              | Ca. 330 cm                      |                                     |
| Total weight                | Ca. 8,9 ton                     |                                     |
| Container volume            | 8.5 m <sup>3</sup> high-tipper  | To the left on 285 cm               |
| Wheels                      | 500/50 - 17 BKT                 | Opt. 500/45R 22.5 BKT Ridemax       |
| Pendel tandem               | Pendel tandem                   | Opt. Forced steering or lift axle   |
| Forest crane 2 hand control | Joysticks electric proportional | Opt. Radio elec. proportional       |
| Outreach                    | 630 cm                          | Telescopic                          |
| Wood grapple type           | Farma 0,16 4 tooth              | Opt. "more tooth grapple"           |
| Rotator                     | 3 ton, endless                  | Opt. Flange mounting                |
| Lights                      | LED                             | Opt. LED work lights                |
| Support legs                | 2 at the front                  | Incl. uncoupling Combi from tractor |
| Min./Max. HP                | 100 - 180 HP                    | 1000 PTO                            |
| Hitch coupling              | Low, Ø 50 mm Piton-hitch        | Opt. K80 ball coupling              |
| Colors standard             | Frame grey, Container TP Red    | All side powder coated              |



